

ÖZLEM[®]

FABRIC

FURNILANA



Task Seating



Soft Seating



Panels



Environmental



Cigarette & Match



Acoustic



Curtains


FURNILANA



DOLLY
271327



SILVER
027057



GREY
027058



ANTRACIDE
027151



STEPPE
117489



BABY CAMEL
119069



STORM
118933



ICE MENTHA
118937




TAPESTRY
118914




APRICOT
118924



LAMA
117520



PINKY
118884




SAGE
118892



BUTTER
118894



SALMON
119035



BLOSSOM
119037



SKY
118876



AQUA MARINE
118197



TURQUOISE
117547



TOPAZ
117679



ADRIATIC
118194



SODA LIFE
117544




OXFORD
117519



AVOCADO
117765

FURNILANA



OLIVE
117397



MOSS
117446



KIWI
117485



GOLDFISH
271229



OXIDE
117491



LIME
117396



AMBER
117398



PUMPKIN
117399



BEESWAX
117761



MARS
117546



CAPIA
117393



BURGUNDY
117464




MARSALA
117459



RASPBERRY
117543



ORCHID
117394




DAMSON
117514




BLACKBERRY
117517




WALNUT
117518



OBSIDIAN
110225



TRUFF
117401



FUME
117400

EN	TR	FR	ES
Composition %80 Wool %20 Polyamide Non Metallic Dyestuffs	Karışım %80 Yün %20 Poliamid Zararlı Metal Bulundurmayan Boyalar Kullanılmıştır	Composition %80 Laine %20 Polyamid Teintures non métalliques	Composición %80 Lana %20 Polyamid Tintes no metálicos
Width 140 cm	En 140 cm	Largeur 140 cm	Ancho 140 cm
Weight 460g/m2 ± 5% (640g/lin.m ±5%)	Ağırlık 460g/m2 ± 5% (640g/lin.m ±5%)	Poids 460g/m2 ± 5% (640g/m.l ±5%)	Peso 460g/m2 ± 5% (640g/lin.m ±5%)
Abrasion Resistance 50.000 Martindale cycles (ISO 12947-2:1998)	Abrazyon 50.000 Martindale cycles (ISO 12947-2:1998)	Résistance á l'abrasion 50.000 Martindale tours (ISO 12947-2:1998)	Resistencia a la abrasión 50.000 Martindale ciclos (ISO 12947-2:1998)
Pilling 4/5 (ISO 12945-2:2000)	Pilling 4/5 (ISO 12945-2:2000)	Boulochage 4/5 (ISO 12945-2:2000)	Pilling 4/5 (ISO 12945-2:2000)
Color Fastness to Rubbing Dry: 4 (BS EN ISO 105 X12:2002) Wet: 4 (BS EN ISO 105 X12:2002)	Sürtme Renk Haslıđı Kuru: 4 (BS EN ISO 105 X12:2002) Yaş: 4 (BS EN ISO 105 X12:2002)	Solidité des couleurs au frottement Sec: 4 (BS EN ISO 105 X12:2002) Mouillé: 4 (BS EN ISO 105 X12:2002)	Solidez del color al rozamiento Seco: 4 (BS EN ISO 105 X12:2002) Húmedo: 4 (BS EN ISO 105 X12:2002)
Light Fastness 5 (BS EN ISO 105 B02:2014)	Işık Haslıđı 5 (BS EN ISO 105 B02:2014)	Solidité à la lumière 5 (BS EN ISO 105 B02:2014)	Solidez a la luz 5 (BS EN ISO 105 B02:2014)
Flammability BS EN 1021 -1:2014 Cigarette BS EN 1021 -2:2014 Match	Yanmazlık BS EN 1021 -1:2014 Sigara BS EN 1021 -2:2014 Kibrit	Flammabilité BS EN 1021 -1:2014 Cigarette BS EN 1021 -2:2014 Allumette	Inflamabilidad BS EN 1021 -1:2014 Cigarillo BS EN 1021 -2:2014 Cerilla
Cleaning Vacuum regularly. Professionally dry clean or wipe clean with a damp cloth	Temizleme Profesyonel kuru temizleme yapınız. Islak temiz bez ile silinebilir.	Nettoyage Aspirez régulièrement. Nettoyage à sec professionnel. Autrement, essuyer avec un tissu humide.	Limpieza Limpiar con aspirador con regularidad. Limpiar en seco, o bien lavar con un paño húmedo
Notes Shade variations may occur batch to batch within commercial tolerances.	Not Üretimler arasında kabul edilebilir seviyede renk ton farkları oluşabilir.	Remarque Une Variation de couleurs peut provenir Commercialement tolérable	Nota Las variaciones de lote a lote en la sombra se puede producir dentro de tolerancias comerciales.

ÖZLEM®

FABRIC



ÖZLEM.FABRIC

Özlem Kumaş San. Tic. Ltd. Şti.
Tekstilcent Koza Plaza B Blok
Kat:31 Esenler 34235
İSTANBUL / TURKEY

T : +90 212 438 5 438
E : fabric@ozlemkumas.com
W : www.ozlemkumas.com